

ARCADEX PRO | GRX 820/822 DISC 1X12SP | YTB85



The image shown is indicative only. Components and graphic detail may differ from actual model. Bianchi reserves the right to amend specifications and/or prices.

COLOR	AF - AW	CASSETTE / FREEWHEEL	Shimano CS-M7100-12 speed, 11-51T Driver body Interface: MicroSpline
FRAME	Arcadex PRO Disc Brake Specification: Flat Mount 140/160 Bottom Bracket Standard: PressFit 86.5 X Ø41 Rear Axle: thru12 OLD (Over-Locknut-Dimension): 142 mm Front Derailleur: Non Compatible Rear Derailleur: SRAM UDH Hanger type Max Chaining Compatibility: 38T-44T Minimum Chainline: 45.5 mm Tire Clearance: ETRTO 622-50 mm SeatPost O.D: Ø27.2 mm Material: Epoxy - SM Carbon Fiber Composite	DISC ROTOR	Shimano SM-RT70 IceTech Hub Interface: Centerlock Rotor Diameter: 160 mm (front&Rear)
HEADSET	Bianchi Custom Acros ICR (Internal Cable Routing) Spacers: 5 mm x1, 10 mm x3 Headtube Cover: Bianchi Custom Compression Ring: 1.125 Inch Top Bearing: Angular contact Bearing 42x52x7 + seal Bottom Bearing: Angular contact Bearing 40x52x7 + seal	WHEELSET	Velomann Terbiu clincher and tubeless ready Rim Diameter: 700C Material: Carbon Rim Height: 30 mm Inner Width Channel: 25 mm
FORK	Bianchi Arcadex Fork Disc Brake Specification: Flat Mount 140/160 Front Axle: thru12 OLD (Over-Locknut-Dimension): 100 mm Tire Clearance: ETRTO 622-42 mm Steer tube Diameter: 1 1/8" Material: Epoxy - SM Carbon Fiber Composite	TIRE	Pirelli Cinturato™ GRAVEL M Classic, 45-622 tan sidewall
SHIFTER	Shimano GRX 820 ST/BL-RX820	STEM	Velomann AICR Alloy Rise: -2° Steerer Diameter: 1-1/8" (28.6 mm) HB interface Diameter: 1-1/4" (31.8 mm) Stem Lengths: 80 mm-XS(47), 90 mm-SM(51), 100 mm-MD(55), 110 mm-LG(58), 120 mm-XL(61)
REAR DERAILLEUR	Shimano GRX 822 RD-RX822, SGS Maximum Cassette Sprocket 51T	HANDLEBAR	Velomann Gravel ICR Alloy Flare: 16° Drop: 130 mm Reach 70 mm Interface Diameter: 1 1/4" (31.8 mm) HandleBar Widths: 400 - SX(47) SM(51), 420 - MD(55) LG(58), 440 - XL(61)
CRANKSET	Shimano GRX 820 FC-RX820-1,40T Crank Length: 170 mm-XS(47)-SM(51), 172.5 mm-MD(55)-LG(58), 175 mm-XL(61)	TAPE	Bianchi Hexagon tape 2.5 mm thickness, Full black
BOTTOM BRACKET	Shimano SM-BB72-41B, press fit	SEATPOST	Velomann Carbon UD SeatPost O.D: Ø27.2 mm Seatpost lengths: 300 mm-SX(47), 350 mm- SM(51) MD(55), 400 mm-LG(58) XL(61)
CHAIN	Shimano CN-M7100	SADDLE	Velomann MITORA 149 HI cover: soft touch padding: foam shell: nylon carbon rails: Aisi Steel length: 250 mm width: 149 mm weight: 230g ± 2